



FS CGF Release Oil 10

FS CGF Release Oil 10 contains a unique blend of oils and esters which aid in the release of dies, molds for fine tiles, and concrete work. FS CGF Release Oil 10 may be sprayed or brushed onto molds a day or two in advance of production. The molds will still release without bubbles, blemishing, or fracturing of the tile or concrete surface.

NOTE: FS CGF Release Oil 10 is NOT to be used in the diecasting of hot metals. This product is for tiles and concrete only.

TYPICAL PROPERTIES

Fluid Type:	Mold Release Agent
Flash Point . (C.O.C.):	>380 Degrees F.
Typical Viscosity, cSt @ 40° C:	10
ISO VG#:	10
Specific Gravity:	0.845
ASTM Color:	(.5) Pail Yellow/ Clear
Smell:	Faint Oil Smell

STORAGE: FS CGF Release Oil 10 should be stored at room temperatures (between 55 to 95 °F). Keep away from sparks, open flames, and other sources of ignition as product and empty containers could contain combustible, flammable, or ignitable substances. Do not weld or cut empty drums.

HEALTH & SAFETY: Please refer to the Safety Data Sheet (SDS) for additional information.

Warranty: Because conditions of use are beyond our control, no representation or warranty is made in connection with the use of this product. Technical information and recommendations are believed to be accurate, but are not guaranteed.

July, 2019 R: Product Tech Letterhead 2019/ CGF Release Oil 10