

FS HTB Fluid (Canada)

Description:

FS HTB Fluid is a high-quality, multifunctional fluid, specially formulated for use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment employing a common fluid reservoir. FS HTB Fluid is formulated with high-viscosity-index base oils, viscosity index improver, anti-foam agent, pour point depressant, and a special additive package providing outstanding oxidation and corrosion inhibition, anti-wear properties, and frictional characteristics.

Features and Benefits:

- Lower operating costs
- Longer equipment life
- Chatter-free operation
- Compatibility
- Reduced downtime
- Smoother operation

Product Availability:

- 18.9 L Pail
- 208.2 L Drum
- 1,003.1 L Tote

Meet or Exceeds:

- AGCO-Allis, Deutz-Allis Power Fluid 821, 821XL
- J.I. Case TCH JIC-145/MS-1210, TFD JIC185/MS-1204, TFDII/MS-1205, Powerguard PTF/MS-1206
- International Harvester Hy-Tran/B-6
- Case/IH B-6, MS-1206, MS-1207/Hy-Tran Plus
- John Deere J14B, J20A, HYGARD, J21A, J20C, 303 Fluid
- Ford, Ford-New Holland M2C41-B, M2C48B, M2C53-A, M2C86-C, M2C134-C/D
- Massey Ferguson M-1129A, M-1127, M1135, M-1110, M1138, M-
- 1141/Permatran III Hydraulic/Trans Fluid, SEMS 17001
- White-Oliver Q-1705, Q-1722, Q-1766, Q-
- 1802, Q-1826, TYPE 55, White Ag One Universal Fluid
- Versatile Hygear Fluid, 23M
- Kubota Universal Transdraulic Fluid, UDT Fluid
- Caterpillar TO-2 Fluid
- Sperry Vickers I-286-S, M-2950-S
- Denison HF-0, HF-1, HF-2
- Sundstrand Hydraulics
- Cincinnati Milacron
- Can be used in most hydrostatic systems that require ATF

Always check owner's manual for proper recommendation.

Typical Properties:

Test / Description	Specification
Approximate SAE Grade	10W-20
Viscosity @ 100°C (cSt)	9.48
Viscosity @ 40°C (cSt)	57.71
Viscosity Index	147
Density (lb/gal)	7.18
CCS Viscosity (cP)	5,339 @ -20°C
Pour Point (°C)	-45
Pour Point (°F)	-49
Flash Point (°C)	234
Flash Point (°F)	453