

# SAFETY DATA SHEET

## FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40

Revision Date 09/02/2021

### SECTION 1. IDENTIFICATION

Product name : FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40 (Canada)

#### Manufacturer or supplier's details

Forsythe Lubrication Associates Ltd  
120 Chatham Street  
Hamilton ON L8P 2B5  
Canada  
Telephone : 1-905-525-7192

#### Emergency telephone number

Emergency telephone number : CANUTEC 1-888-226-8832  
Poison Control Centre: Consult local telephone directory for emergency number(s).

#### Recommended use of the chemical and restrictions on use

Recommended use : FS SUPREX XP DIESEL ENGINE OIL 15W-40 is a superior quality heavy duty diesel engine oil specifically designed for '07 EPA engine requirements along with improved performance benefits in legacy engines. Application includes modern low emission diesel engines with cooled exhaust gas recirculation and exhaust after treatment technology.

Prepared by : Product Safety: +1 905-491-0565

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	viscous liquid
Colour	light brown
Odour	Mild petroleum oil like.

#### GHS classification in accordance with the Hazardous Products Regulations

Not a hazardous substance or mixture.

#### GHS label elements

Not a hazardous substance or mixture.

# SAFETY DATA SHEET

## FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40

Revision Date 09/02/2021

### Potential Health Effects

Primary Routes of Entry : Eye contact  
Ingestion  
Inhalation Skin contact

Aggravated Medical Condition : None known.

### Other hazards

None known.

### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

### ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	70 - 90
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	30 - 50
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high viscosity	72623-85-9	30 - 50
A mixture of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4hydroxyphenyl)propionate	125643-61-0	2.5 - 5
bis(nonylphenyl)amine	36878-20-3	1 - 2.5
Zinc alkyldithiophosphate	113706-15-3	1 - 2.5
distillates (petroleum), solventdewaxed heavy paraffinic	64742-65-0	1 - 5

## SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.  
Artificial respiration and/or oxygen may be necessary. Seek medical advice.

# SAFETY DATA SHEET

## FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40

Revision Date 09/02/2021

---

In case of skin contact	: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	: Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	: Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	: First aider needs to protect himself.

---

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media :	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: No information available.
Specific hazards during firefighting	: Cool closed containers exposed to fire with water spray.
Hazardous combustion products	: Carbon oxides (CO, CO <sub>2</sub> ), nitrogen oxides (NO <sub>x</sub> ), sulphur oxides (SO <sub>x</sub> ), phosphorus oxides (PO <sub>x</sub> ), sulphur compounds (H <sub>2</sub> S), zinc oxides (ZnO <sub>x</sub> ), metal oxides, hydrocarbons, smoke and irritating vapours as products of incomplete combustion.
Further information	: Prevent fire extinguishing water from contaminating surface water or the ground water system.

# SAFETY DATA SHEET

## FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40

Revision Date 09/02/2021

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Evacuate personnel to safe areas.  
Material can create slippery conditions.  
Mark the contaminated area with signs and prevent access to unauthorized personnel.  
Only qualified personnel equipped with suitable protective equipment may intervene.
- Environmental precautions : Do not allow uncontrolled discharge of product into the environment.
- Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.  
Remove all sources of ignition.  
Soak up with inert absorbent material.  
Non-sparking tools should be used.  
Ensure adequate ventilation.  
Contact the proper local authorities.
- 

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : None known.
- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Use only with adequate ventilation.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin, eyes and clothing.  
Do not ingest.  
Keep away from heat and sources of ignition.  
Keep container closed when not in use.
- Conditions for safe storage : Store in original container.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Keep in a dry, cool and well-ventilated place.  
Keep in properly labelled containers.  
To maintain product quality, do not store in heat or direct sunlight.
-

# SAFETY DATA SHEET

## FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40

Revision Date 09/02/2021

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high viscosity	72623-85-9	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH

# SAFETY DATA SHEET

## FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40

Revision Date 09/02/2021

**Engineering measures** : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

### Personal protective equipment

**Respiratory protection** : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Filter type** : organic vapour filter

**Hand protection**

**Material** : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

**Remarks**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection**

: Wear face-shield and protective suit for abnormal processing problems.

**Skin and body protection**

: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Protective measures**

: Wash contaminated clothing before re-use.

**Hygiene measures**

: Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : viscous liquid

**Colour** : light brown

**Odour** : Mild petroleum oil like.

**Odour Threshold** : No data available

**pH** : No data available

**Pour point** : -36 °C (-33 °F)

**Boiling point/boiling range** : No data available

# SAFETY DATA SHEET

## FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40

Revision Date 09/02/2021

---

Flash point : 228 °C (442 °F)  
Method: Cleveland open cup

Fire Point : 247 °C (477 °F)

Evaporation rate : No data available

Auto-ignition temperature : No data available

# SAFETY DATA SHEET

## FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40

Revision Date 09/02/2021

---

Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8711 kg/l (15 °C / 59 °F)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: noctanol/water	:	No data available
Viscosity		
Viscosity, kinematic	:	118.2 cSt (40 °C / 104 °F)
		15.6 cSt (100 °C / 212 °F)
Explosive properties	:	Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

---

### SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents and reducing agents.
Hazardous decomposition products	:	May release COx, H2S, smoke and irritating vapours when heated to decomposition.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

Information on likely routes of exposure	:	Eye contact Ingestion Inhalation Skin contact
--	---	--



# SAFETY DATA SHEET

## FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40

Revision Date 09/02/2021

### Acute toxicity

#### Product:

- Acute oral toxicity : Remarks: No data available
- Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: No data available
- Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: No data available

#### Components: lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,
- Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist
- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,
- #### **lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:**
- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,
- Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,
- #### **lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high viscosity:**
- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,
- Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,
- #### **distillates (petroleum), solvent-dewaxed heavy paraffinic:**
- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg,

### Skin corrosion/irritation

#### Product:

- Remarks : No data available

### Serious eye damage/eye irritation

#### Product:

- Remarks : No data available

# SAFETY DATA SHEET

## FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40

Revision Date 09/02/2021

---

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity No

data available

### STOT - single exposure

No data available

### STOT - repeated exposure No

data available

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other : Remarks: No data available aquatic  
invertebrates

Toxicity to algae : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

### Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

# SAFETY DATA SHEET

## FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40

Revision Date 09/02/2021

---

### Other adverse effects

No data available

### SECTION 13. DISPOSAL CONSIDERATIONS

---

#### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Offer surplus and non-recyclable solutions to a licensed disposal company.  
Waste must be classified and labelled prior to recycling or disposal.  
Send to a licensed waste management company.  
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### National Regulations TDG

Not regulated as a dangerous good

---

### SECTION 15. REGULATORY INFORMATION

#### The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

---

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)

Page:

# SAFETY DATA SHEET

## FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40

Revision Date 09/02/2021

---

CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

ACGIH / TWA : 8-hour, time-weighted average

CA AB OEL / TWA : 8-hour Occupational exposure limit

CA AB OEL / STEL : 15-minute occupational exposure limit

CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan);

# SAFETY DATA SHEET

## FS SUPREX XP DIESEL ENGINE OIL SAE 15W-40

Revision Date 09/02/2021

ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - SelfAccelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Prepared by : Operations: +1 905-525-7192

Revision Date : 2020/01/03

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. CA / EN