



# FS CG 4221

## RUST PREVENTATIVE

**FS CG 4221** is formulated with a proprietary blend of anti-corrosion additives, base oils, and solvent, making for an easily applied full coverage rust preventative. This product is ideal for use when parts have been processed through water solutions, and when they will be exposed to changes in humidity, salt corrosion, or acidic environments.

**FS CG 4221** deposits a thin, transparent, light oil film that is not easily disturbed during shipping and handling. Additionally, the product is non-staining and is safe to use on coiled or stacked metals. It is also non-corrosive to a variety of non-ferrous metals including copper, aluminum, zinc, magnesium, brass, and cadmium.

**FS CG 4221** is to be used straight, do not cut back with solvent, water or oil.

### TYPICAL PHYSICAL PROPERTIES

Fluid Type:	Rust Preventative
Specific Gravity:	0.82
Flash Point:	140 Degrees F
ASTM Color:	2.5
Water Displacement:	Pass
Humidity Cabinet, ASTM D1748:	40 Days
Salt Spray, 5%, ASTM B117:	60 Hours
Acid Atmosphere Protection:	Pass, up to 30 hours
Indoor Protection:	12+ months
Nickel Metal Reactivity:	No reaction in laboratory
Barium/ Heavy Metals:	Barium Free/ No heavy metals in product
Application:	Parts may be sprayed or dipped

**STORAGE:** **FS CG 4221** should be stored at room temperatures (between 55 to 95 °F). Keep away from sparks, open flames, and other sources of ignition as product and empty containers could contain combustible, flammable, or ignitable substances. Do not weld or cut empty drums.

**HEALTH & SAFETY:** Please refer to the Safety Data Sheet (SDS) for additional information.

**Warranty:** Because conditions of use are beyond our control no representation or warranty is made in connection with the use of this product. Technical information and recommendations are believed to be accurate but are not guaranteed.

July, 2015

R: Product Tech Letterhead 2015/FS CG 4221