

FS Low Viscosity Power Fluid

Description

Low Viscosity Power Fluid is a superior-quality, multifunctional fluid, specially formulated for use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment employing a common fluid reservoir.

It is designed for use in low-temperature applications and wherever a fluid meeting John Deere J20D is specified.

It is formulated with a high viscosity index, premium group II base oils, a superior viscosity index improver, an anti-foam agent, a pour point depressant, and a special additive package, providing exceptional oxidation and corrosion inhibition, anti-wear properties, and frictional characteristics.

Features and Benefits:

- Lower operating costs
- Longer equipment life
- Excellent low-temperature pumpability
- Superior oxidation stability and fluid life
- Chatter-free operation
- Compatibility
- Reduced downtime
- Smoother operation
- Oil durability

Meets or Exceeds:

- John Deere J20D
- Caterpillar TO-2 Fluid
- Sperry Vickers I-286-S, M-2950-S
- Denison HF-0, HF-1, HF-2
- Sundstrand Hydraulics
- Cincinnati Milacron
- Can be used in most hydrostatic systems that require ATF

Always check owner's manual for proper recommendation.

Product Availability:

5 Gal. Pail	Item #156470
55-gal. Drum	Item #156460
265-gal. Totes	Item #156461
Bulk	Item #156462

Typical Properties

Test / Description	Specification
Viscosity @ 100°C (cSt)	7.0
Viscosity @ 40°C (cSt)	37.5
Viscosity Index	150
Density (lb/gal)	7.29
CCS Viscosity (cP)	NA
Pour Point (°C)	-39
Pour Point (°F)	-38
Flash Point (°C)	185
Flash Point (°F)	365
Brookfield @ -25°C (cP)	1,300
Brookfield @ -40°C (cP)	16,000